

Rainbow II™ Wireless Monitor

transvideo

Zone Industrielle
27135 Verneuil sur Avre
FRANCE
Tel: +33 (0) 2 3232 2761
Fax: +33 (0) 2 3260 1479

www.transvideointl.com

Transvideo 6.5" Rainbow II™ Wireless Monitor

is available with an integrated Titan video receiver or transmitter.

Both models feature an XLR4 for power input and can be ordered with professional battery sockets or with Smart Mini DV battery backs.

Transvideo 6.5" Rainbow™II Wireless Monitor with built-in Receiver

can be quickly switched between 4 channels. In addition, 2 external signals can also be wired to the monitor.

Two video signals can be fed simultaneously to the Transvideo 6.5" Rainbow™II Wireless Monitor with built-in Transmitter. The image displayed on the monitor is also the one transmitted. The built-in transmitter can be set to 4 different channels.



NOW AVAILABLE

The Titan transmitter/receiver is the first multi-directional real time microwave system broadcasting through obstacles without desynchronization of the video.

Transvideo 6.5" Rainbow™II Wireless Monitors feature a professional native 16/9 LCD monitor, switchable between 16/9, 4:3 and Anamorphic.

The image can be displayed in Full, Broadcast or Under-Scan Modes. In Full and Under-scan modes the Operator has the comfort to know the full video image is displayed without any cropping.

Basic adjustments for Brightness, Contrast, Saturation and Hue in NTSC as well as more advanced features such as Sharpness, Flips, Display modes and Ratios are easily accessed.

The Lock function prevents accidental activation of the digital mode: once "locked" the monitor operates like a 6.5" 16/9 Rainbow I™.

This monitor is designed to be used without hood in full sun.

With the widest viewing angle available and no hood necessary, it can be looked at simultaneously by several viewers.

Light, compact and very rugged, the 6.5" Rainbow™II Wireless Monitor is the perfect Director's monitor.

TITAN PERFORMANCES

- Real Time transmission through residential walls, floors, ceilings or crowds without picture interruption.
- Range: 300m (1000ft) line of sight.

MONITOR MAIN FEATURES

- 16/9 native screen switchable 4:3 and Anamorphic
- Full, Broadcast & Under-Scan Modes
- Zoom Function
- Active Matrix TFT
- Viewable in full sun without hood.
- Extra-rugged construction

SPECIFICATIONS	Inputs:	1(TX) or 2 (RX) Composite (BNC), 1 Composite (Hirose 6)
	Output:	1 Video out (Hirose 6)
	Nominal Levels:	Composite, 1V / 75Ω
	LCD Screen: Useful diagonal Viewing angle Brightness	6.5" 16/9 (14.7 cm) +/- 65° (H) + 50°/-65° (V) SuperBright: typ. 900 NIT High-Brightness: typ.420 NIT
	Mechanic (w/o battery socket): Dimensions in mm or inches Weight	163(l) x 100(h) x 58.5(d) or 6.4 (l) x 3.9 (h) x 2.3 (d) 800 g , 1.75 lbs
	Power Input / consumption	XLR4 connector (-1,+4), range: 10 to 36v DC / 15W

For complete specs, refer to the Titan and 6.5" 16/9 Rainbow II brochures.